



The Indian Hume Pipe Co. Ltd.

502 C, 5th Floor, Lingapur House, 3-6-237, Amrutha Estates, Himayathnagar, Hyderabad-500 029 - (A.P.)
Tel : (040) 2326 2384 / 85, Fax : (040) - 23262385 / 4015 6952 Email : ihphnr@indianhumepipe.com

PERFORMANCE CERTIFICATE

TO WHOM SO EVER IT MAY CONCERN

This is to certify that M/s.Durga Engineering Company, Ichapur Road, Canal Side, Howrah-711 104 has supplied the following DURGA make valves for Manufacturing, Supplying, Lowering, Laying, Jointing, Testing and commissioning of 450mm dia MS Pumping main from Jawaharnagar to Rajiv Gruhakalpa Sump at Ahmedguda, Nizampet, Balajinagar - Kowkur, Sainikpuri Balajinagar to Rajiv Gruhakalpa Housing colonies (HMWSSB) vide our Purchase Order No.1)HP/232/F25/DEPL/HIM, Dated: 13.06.2008. 2) HP/233/F25/DEPL/HIM, Dt:13.06.2008. 3) HP/234/F25/DEPL/HIM, Dt: 13.06.2008. 4) HP/231/F25/DEPL/HIM, Dt: 13.06.2008.

S.No	Description of Item	Quantity
1	D.I Air Valve with body and cover in ductile iron of Grade SG 400/12 and subsequent revisions. All internal parts such as float, shell, all cover bolts of stainless steel and gaskets and seal of EPDM. Epoxy powder coating (EP-P) inside and outside colour blue.	
a	80mm of PN-1.0	38
b	100mm of PN-1.0	10
2	D.I D/F Butterfly Double eccentrically disc. With renewable soft seal on the disc on body seat face of nickel weld overlay micro finished with powder of liquid epoxy coating with minimum thickness of 250 microns applied on both body and disc inside and outside. Face to face dimensions as per EN 558-1 basis series 14 (DIN 3202 F4) or AWWA C 504: 80 OR BS 5155 OR IS 13095.	
a	400mm of PN-1.0	16
b	450mm of PN-1.0	6
c	600mm of PN-1.0	8
3	D.I D/F Gate Valves (Soft Seated), Resilient seated Gate Valve (Sluice Valve) with body bonnet of Ductile Cast Iron of Gr.GGG40 wedges fully rubber lined with EPDM.	
a	80mm of PN-1.0	38
b	100mm of PN-1.0	10
c	150mm of PN-1.0	8
d	200mm of PN-1.0	6
e	300mm of PN-1.0	8
f	350mm of PN-1.0	3


Date of commissioning : **18/02/2009**

Value of Purchase Order : **Rs.63,56,110.00**

The above valves are functioning satisfactorily from the date of commissioning.

For THE INDIAN HUME PIPE CO. LTD.,

[G.PUNDAREEKAM]
General Manager *



M. Durga Engineering Company

Authorized Signatory



The Indian Hume Pipe Co. Ltd.

502 C, 5th Floor, Lingapur House, 3-6-237, Amrutha Estates, Himayathnagar, Hyderabad-500 029 - (A.P.)
Tel : (040) 2326 2384 / 85. Fax : (040) - 23262385 / 4015 6952 Email : ihphnr@indianhumepipe.com

PERFORMANCE CERTIFICATE

TO WHOM SO EVER IT MAY CONCERN

This is to certify that M/s. DURGA ENGINEERING COMPANY, Ichapur Road , Canal side, HOWRAH -711104 has supplied the DURGA make Ductile Iron Single Chamber Air valves, Butterfly Valves, Soft seated resilient Gate Valves to "Providing Water Supply in IT & other sector in and around Gachibowli and Manikonda areas by laying 900/800/600mm dia & MS & 600/500/300mm dia DI K7 water supply pipeline from Prashasan Nagar GLSR to Financial District, Manikonda and IVR Prime Construction at Gachibowli including construction of 10ML capacity RCC GLSR, beside IVR Prime Construction, and 5 ML capacity RCC GLSR, Pump Room, Financial District, Manikonda - (HMWSSB)" vide our Purchase order IHP/355/F25/DEPL/HIM Dated 24.07.2008 as details follows:

Sl.No.	Description	QTY
1	DI Air Valve with body and cover of ductile Iron of grade GGG-40 IS:210/SG Iron 1865-400/12 or equivalent grade with all internal parts such as float, shell etc., all cover bolts of austenitic alloy steel, DN 50 float, and gaskets and seals of EPDM. Epoxy powder coating (EP-P) inside and outside colour blue. With and no.1 Of same dia DI D/F Resilient Seated soft sealing Isolating Sluice Valve (Soft Seated), Dimension confirming to IS 14846-2000.	
	100mm of PN- 1.6	21 Nos
	150mm of PN- 1.6	15 Nos
2	DI D/F Butterfly Valve double eccentric disc renewable soft seal on the disc and the body seat face of nickel weld overlay micro finished with epoxy coating with minimum thickness of 250 microns applied both body and disc inside and outside. Face to Face dimensions as per EN 558-1 basic series 14 (DIN 3202 F4) or AWWA C 504: 80 or BS 5155 OR IS 13095.	
	400mm of PN-1.6	18 Nos
	450mm of PN-1.6	4 Nos
	500mm of PN-1.6	6 Nos
	600mm of PN-1.6	8 Nos
	700mm of PN-1.6	18 Nos
3	DI D/F Resilient seated soft sealing Gate Valve (Soft Seated) PN-1.6 rated dimensions confirming to IS: 14846-2000, with body bonnet of ductile cast iron of grade GGG-40 of IS-210/SG iron 1865-400/12 or equivalent grade, wedge fully rubber sealed with EPDM and seals of NBR with Epoxy powder coated both inside and outside with pocket less body passage confirming to IS: 14846-2000/DIN 3202 F4.	
	300mm of PN-1.6	15 Nos

Value of the Purchase order : **Rs. 1, 08, 00,997.00/-**

Date of Commissioning : **31.12.2010**

The above valves supplied and are functioning satisfactorily from date of commissioning.

For THE INDIAN HUME PIPE CO. LTD.,

[G.PUNDAREEKAM]
General Manager

The Durga Engineering Company

Authorized Signatory



The Indian Hume Pipe Co. Ltd.

502 C, 5th Floor, Lingapur House, 3-6-237, Amrutha Estates, Himayathnagar, Hyderabad-500 029 - (A.P.)
Tel : (040) 2326 2384 / 85, Fax : (040) - 23262385 / 4015 6952 Email : ihphnr@indianhumepipe.com

PERFORMANCE CERTIFICATE TO WHOM SO EVER IT MAY CONCERN

This is to certify that M/s. **DURGA ENGINEERING COMPANY**, Ichapur Road, Canal Side, Howrah-711104 has supplied the DURGA make Ductile iron & Cast steel valves to "**J.C.NAGI REDDY DRINKING WATER SUPPLY SCHEME IN ANATHAPUR DISTRICT**" (Rural Water Supply & Sanitation Department, Government of Andhra Pradesh) Vide our purchase order **IHP/864/F25/DEPL/HIM** Dated **05.03.2008** Value of **Rs.2,78,88,113.00** as details follows:

Sl.No.	Description	QTY(Nos)
1	DI Single Chamber Air Release Valve with body and cover of ductile Iron of grade SG 400/12 and subsequent revisions. All internal parts such as float, shell etc., all cover bolts of austenitic alloy steel, and gaskets and seals of EPDM. Epoxy powder coating (EP-P) inside and outside color blue.	
	100mm of PN- 2.5	69
	150mm of PN - 2.5	140
	200mm of PN- 2.5	40
2	Cast Carbon Steel Scour Valve (with Dismantling Joints)	
	300mm of PN-25	16
	400mm of PN-25	18
	500mm of PN-25	06
3	DI D/F Butterfly Valve double eccentrically disc renewable soft seal on the disc and the body seat face of nickel weld overlay micro finished with epoxy coating with minimum thickness of 250 microns applied both body and disc inside and outside. Face to Face dimensions as per AWWA C 504 (with Dismantling Joints)	
	150mm of PN - 2.5	01
	350mm of PN - 2.5	01
	500mm of PN-2.5	16
	600mm of PN-2.5	25
	1000mm of PN-2.5	02

Date of Purchase Order : 05.03.2008
Date of manufacturing clearance : 25.07.2008
Date of Inspection by department : 17.08.2008 & 13.09.2008
Date of receipt of Valves at site : 25.08.2008 & 17.09.2008

All the Valves were received within two months from the date of manufacturing clearance as per our delivery schedule. The delay in giving manufacturing clearance was due to non availability of site clearance for laying of pipes at site.

For THE INDIAN HUME PIPE CO. LTD.

(G. PUNDAREEKAM)
GENERAL MANAGER

Dated: 16.03.2011