KARNATAKA URBAN WATER SUPPLY AND DRAINAGE BOARD, DN, VIJAYAPUR

Badikaman Road, Opp.Kakakarkanis Kalyan Mantap, E-Mail:- kuwsdbeebjp@Yahoo.com

No.KWB/EE-VJP/Tech/Durga Valves/ 2015-16/ 3968

Date: /9-01-2016

PERFORMANCE CERTIFICATE MAY TO WHOM SO EVER IT MY CONCERN

~*~*~

This is to certify that M/s. Durga Valves Private Limited, Howrah (WB) has supplied the following valves to Karnataka Urban Water Supply & Drainage Board, Division, Bijapur-586101, for pump house at Kolhar, Mulwad and on pure water rising main under Improvements Water Supply Scheme to Bijapur city (UIDSSMT).

SI.No.	Type of Valves	Quantity
1	900 mm dia DVPL DI D/F Butterfly valve PN-1 with gear and hand wheel	6 Nos.
2	150mm dia DVPL DI single chamber Air valve, PN-1.6	40 Nos.
3	150mm dia DVPL DI Sluice valve, PN-1.6	40 Nos.
4	150mm dia DVPL DI Sluice valve, PN-2.5	23 Nos.
5	150mm dia DVPL DI single chamber Air valve, PN-2.5	23 Nos.
6	300mm dia DVPL DI Sluice valve, PN-1.6	6 Nos.
7	300mm dia DVPL DI Sluice valve, PN-2.5	10 Nos.

The above pump houses and rising main are commissioned in the month of November-2012 all the valves are working satisfactorily.

Executive Engineer, KUWS & D Board, Division, Vijayapur.





Office of the Executive Engineer, KUWS&DB, Division, Ramakrishna Ashrama Road, Tumkur – 570005 Ph:0816-2200209

Karnataka Urban Water Supply & Drainage Board

Ref:No.KWB/EE/TMK/STR/ 1272

/2011-12/Dt. 13 · 12 · 11 .

WORK DONE CERTIFICATE::

This is to certify that M/s. Durga Valves Pvt., Ltd., Ranigunj, Secundrabad, A.P. have supplied the materials as per Tender specification statisfactorily.

SI.	Details of Supplies	Remarks
No.		Supply of D.I. Butterfly valves & D.I.Sluice valves for the work of
1.	Name of the work	
		Providing IInd stage water supply scheme to Tumkur city with
		Hemavathy River as source.
2.	Contract Value	Rs.80,45,000.00
3.	Date of Agreement	19/2011-12 Dt.05-08-2011.
4.	Contract period	60 days
5	Specification	Supply & Delivery of Ductile iron D/F, double eccentric, integral seat design butterfly valves Durga make conforming to DIN 3354/IS 13095 with Body, disc and seat, retaining ring of Ductile Iron GGG-40, renewable soft seal on the disc and Body seat face of nickel weld overlay micro finished, with powder or liquid Epoxy coating with minimum thickness of 250 microns applied on both body and disc inside and outside, shaft of stainless steel DIN W 1.4021 micron, Face to Face dimensions as per EN558-1 basic series 14 (DIN 3203 F4) or AWWA C 504:80 or BS 5155 or IS 13095.
		Supply & Delivery of Resillent seated soft sealing a D.I. Sluice Valves of Durga make as per BS 5163, DIN 3230 with body, bonnet of D.I. of grade GGG50, wedge having core of DI GGG-50 & integral wedge nut of Brass CZ132 to BS 2878 with fully encapsulated by Vulcanized EPDM chlorine resistant rubber and seals of NBR and the valves should be of vaccum tight and 100% leak proof with face dimensions as per BS 5163-89/IS 14846-2000/DIN 3202 F4/F5. The stem sealing should be with toroldal sealing rings (Minimum 3 'O'rings) All the valves should be electrostatically applied epoxy coated to DIN-30677 both inside and outside with pocket less body passage. The Flange connections as per IS 1538/ISO 7005. The valves supplied with galvanized bolts and nuts of GKW/KITO/NEXO/TECHMAN. Above 300mm dia, valves provided with Gear Box and lubricated for life time.
	;	

6.	Total value of the	Rs.80,45,000.00
	work completed	
7.	Details of supplies	450mm dia D.I .Butterfly valve PN 1.0 - 3 Nos
		400 mm dia D.I. Sluice valve PN 1.0 - 17 Nos
		350 mm dla D.I. Sluice valve PN 1.0 - 24 Nos -

This certificate is issued on the specific request made by the Supplier for the purpose of tendering Only.

K.U.W.S. & D. Board, Division,
Tumkur.